



Gooseneck Dump Trailers



Standard Features

- Electric Brakes on all Axles
- Slipper Suspension
- Barn Doors with Cam Lock
- Two-way Gate included with 6.5' & 83" Models
- 12,000 lbs. Jack
- Adjustable 2-5/16" Gooseneck Coupler
- Ramp Kit Included with 83" Models
- Heavy Gauge Floor Included on 83" Models
- Lockable Toolbox
- Interstate Extreme Cycle Battery
- 3,000 psi Hydraulic Power Pack, 20' Hand Remote
- 5" Hydraulic Cylinder & Scissor Hoist
- 6" Hydraulic Cylinder & Scissor Hoist - 16' Models
- Shielded Tarp & Roller, (4) Heavy Duty D-Rings
- Spare Tire Mount
- Powder Coated
- Sealed Beam L.E.D. Lights and Harness System
- Transport Canada & DOT Approved Lighting

Standard Specifications

Width	6 ft. / 6.5 ft. / 83 in.
Length	12 ft. - 16 ft.
Tire Size	ST235/80R16 LRE
Deck Height	25" on 6' & 6.5' Models 29" on 83" Models
Box Height	33" (including 11" Plank)

Options

- Spare Tire
- Ramp Kit (included with 83" Models)
- Torsion Axles (not available with 83" Models)
- Two-way Gate (included with 6.5' & 83" Models)
- Additional D-Rings
- Hydraulic Brakes
- Aluminum Wheels
- 48" High Sides
- 58" High Sides
- Heavy Gauge Floor (included with 83" Models)