



## Tandem Axle Utility Trailers (7,000 lbs. GVWR)



### Standard Features

- Tandem 3,500 lbs. Axles
- 15" Radial Tires
- Electric Brakes on Both Axles
- Slipper Suspension
- 2-5/16" Adjustable Coupler or 3" Lunette Eye
- 2,000 lbs. A-frame Jack
- 4' Split Ramps
- Full Steel Side w/ Tie Rail
- Spare Tire Mount
- Pressure Treated Wood Floor
- (4) D-Rings
- Powder Coated
- Sealed Beam L.E.D. Lights and Harness System
- Transport Canada & DOT Approved Lighting

### Standard Sizes

Size	Model
82" x 12'	UT712-7K
82" x 14'	UT714-7K
82" x 16'	UT716-7K
82" x 18'	UT718-7K
82" x 20'	UT720-7K

### Standard Specifications

Tire Size	ST205/75R15 LRC
Deck Height	17"
Side Height	19" (including tie rail)
Tongue Length	49"
GVWR	7,000 lbs.

### Options

- Spare Tire
- Lockable Toolbox
- 7,000 lbs. Jack
- Additional D-Rings
- Torsion Axles
- Aluminum Wheels



## Tandem Axle Utility Trailers (9,900 lbs. GVWR)



### Standard Features

- Tandem 5,200 lbs. Axles
- 15" Radial Tires
- Electric Brakes on Both Axles
- Slipper Suspension
- 2-5/16" Adjustable Coupler or 3" Lunette Eye
- 12,000 lbs. Jack
- 5' Split Ramps
- Full Steel Side w/ Tie Rail
- Spare Tire Mount
- Pressure Treated Wood Floor
- (4) D-Rings
- Powder Coated
- Sealed Beam L.E.D. Lights and Harness System
- Transport Canada & DOT Approved Lighting

### Standard Sizes

Size	Model
80" x 16'	UT716-10K
80" x 18'	UT718-10K
80" x 20'	UT720-10K
80" x 22'	UT722-10K
80" x 24'	UT724-10K

### Standard Specifications

Tire Size	ST225/75R15 LRD
Deck Height	17"
Side Height	19" (including tie rail)
Tongue Length	49"
GVWR	9,900 lbs.

### Options

- Spare Tire
- Lockable Toolbox
- Hydraulic Brakes
- Additional D-Rings
- Torsion Axles
- Aluminum Wheels



## Tandem Axle Utility Trailers (14,000 lbs. GVWR)



### Standard Features

- Tandem 7,000 lbs. Axles
- 16" Radial Tires
- Electric Brakes on Both Axles
- Slipper Suspension
- 2-5/16" Adjustable Coupler or 3" Lunette Eye
- 12,000 lbs. Jack
- 5' Split Ramps
- Full Steel Side w/ Tie Rail
- Spare Tire Mount
- Pressure Treated Wood Floor
- (4) D-Rings
- Powder Coated
- Sealed Beam L.E.D. Lights and Harness System
- Transport Canada & DOT Approved Lighting

### Standard Sizes

Size	Model
80" x 16'	UT716-14K
80" x 18'	UT718-14K
80" x 20'	UT720-14K
80" x 22'	UT722-14K
80" x 24'	UT724-14K

### Standard Specifications

Tire Size	ST235/80R16 LRD
Deck Height	17"
Side Height	19" (including tie rail)
Tongue Length	49"
GVWR	14,000 lbs.

### Options

- Spare Tire
- Lockable Toolbox
- Hydraulic Brakes
- Additional D-Rings
- Torsion Axles
- Aluminum Wheels